
LED Floodlight without sensor

XLED ONE

Anthracite EAN 4007841 065201 Article number 065201















180° vertical











energy saving

manufacture's warranty steinel.de/garantie

Function description

Astonishingly efficient. Extra-long service life. The XLED ONE wall and ceiling spot impresses with modern LED technology and provides 3000 K and 2550 lm of warm white light from an energy-saving 23 W. The aluminium panel can be tilted through 180°. With high-quality and powerful reflector as well as long-life LEDs (30 years).

Technical specifications

Dimensions (L x W x H)	173 x 229 x 195 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	23 W
Luminous flux	2550 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
With motion detector	No
Photo-cell controller	No

Basic light level function	No
Main light adjustable	No
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 - 40 °C
Housing material	Aluminium
Cover material	Glass transparent
Manufacturer's Warranty	3 years
PU1, net weight	1,11 kg
Version	Anthracite
PU1, EAN	4007841065201

LED Floodlight without sensor

XLED ONE

Anthracite EAN 4007841 065201 Article number 065201



Dimension Drawing

